BHARATI COLLEGE (UNIVERSITY OF DELHI) C-4, JANAKPURI, NEW DELHI-110058

<u>REF.NO: BC/CCTV CAMERA/2025/</u> Dated: 13.06.2025

NOTICE INVITING e-TENDER for Supply and Installation of Video Surveillance with CCTV System (IP BASED) with allied accessories

Online e-tenders are invited on behalf of the Principal, Bharati College, University of Delhi for "Supply and Installation of CCTV (IP Based) Camera with all Accessories" at C-4, Janakpuri, New Delhi-110058.

Document Download: Tender documents may be downloaded from College website www.bharaticollege.du.ac.in (for reference only) or CPPP site https://eprocure.gov.in/eprocure/app as per the schedule. CRITICAL DATE SHEET given on next page.

Manual tender application will NOT be entertained.

The technical bids will be opened first and then the financial bids of technically qualified bidders in shall be opened the presence of the Purchase Committee.

EMD Amount: 36,000.00 (Rupees Thirty Six Thousand Only).

Tender Fee: Rs. 1,000.00 (Rupees One Thousand Only) Not Refundable.

The College Bank details are (Account Name: Bharati College Maintenance Grant A/c, Account Number: 1527000400332120 IFS Code: PUNB0495200, Bank: Punjab National Bank, Bharati College, University of Delhi, Janakpuri, New Delhi-110 058. The bidder shall submit the Tender Fee and EMD Amount through RTGS/NEFT.

Prof. Saloni Gupta Principal

2. Critical Dates:

S. No.	Particulars	Date
1.	Published Date	13.06.2025
2.	Bid Document Download Start Date	13.06.2025
3.	Pre-Bid Meeting	18.06.2025 at 12:00 Noon in Bharati College, University of Delhi, C-4, Janakpuri-110058
4.	Bid Submission Start Date	13.06.2025
5.	Bid Submission End Date	03.07.2025
6.	Bid Opening Date (Technical)	07.07.2025
7.	Bid Opening Date (Financial)	09.07.2025

1. Bid Submission: Bids shall be submitted online only at CPPP website: https://eprocure.gov.in/eprocure/app.

Bidders are advised to follow the 'Special Instructions to the Contractors/Bidders for the e-submission of the bids online' available through the Link:

https://eprocure.gov.in/eprocure/app

Bid documents may be scanned with 100 dpi with black and white option which helps in reducing size of the scanned document.

- 2. Not more than one tender shall be submitted by one contactor or contractors having business relationship. Under no circumstance will father and his son(s) or other close relations who have business relationship with one another (i.e. when one or more partner(s)/director(s) are common) be allowed to tender for the same contract as separate competitors. A breach of this condition will render the tenders of both parties liable to rejection.
- 3. Tenderer who can downloaded the tender from the college website www.bharaticollege.du.ac.in and Central Public Procurement Portal (CPPP) website https://eprocure.gov.in/eprocure/app, shall not tamper/modify the tender form including downloaded price bid template in any manner. In case if the same is found to be tampered/modified in any manner, tender will be completely rejected and EMD would be forfeited and tenderer is liable to be black listed from doing business with the Bharati College/University of Delhi.
- 4. Intending tenderers are advised to keep checking the college website www.bharaticollege.du.ac.in and CPPP website https://eprocure.gov.in/eprocure/app regularly till closing date of submission of tender for any corrigendum / addendum/ amendment.

1. GENERAL TERMS AND CONDITIONS:

Interested bidders may download the tender enquiry documents and submit their tenders online at Central Public Procurement Portal website: https:eprocure.gov.in/eprocure/app and bid online through the portal www.eprocure.gov.in. The bids are invited in a two bid system (Technical and Financial) from reputed firms and are required to be submitted in two parts, namely, (1) Technical Bid and (2) Financial Bid. The Financial Bid should be valid for one year from the date of opening of the Tender. Incomplete bid documents shall be rejected.

2. <u>EARNEST MONEY DEPOSIT (EMD)</u>

Earnest Money Deposit (EMD) for **Rs. 36,000** /- (Rupees Thirty Six Thousand only) in the form of Demand Draft drawn in favour of "Principal, Bharati College" payable at Delhi must reach by hand or through registered post to the address at "The Principal, Bharati College, University of Delhi, C-4, Janakpuri, New Delhi-110058 on or before the scheduled opening of the technical bid. The EMD will be returned to all the unsuccessful bidders at the end of the selection process. However, the EMD shall be forfeited in case the successful bidder withdraws or the details furnished in Annexures are found to be incorrect or false during the tender selection process. No. interest shall be paid on the Earnest Money Deposit and EMD of successful bidder will be returned on receipt of performance guarantee as mentioned below.

3. <u>SECURITY DEPOSIT</u>:

On acceptance of the bid, the successful bidder shall within 15 days from the date of awarding of contract, shall submit 5% as Performance Security Deposit in the form of Demand Draft/Online Transfer in favour of **Principal, Bharati College.** If the contractor fails to provide thesecurity deposit within 15 days from the date of awarding of contract, such failure will be construed as a breach of the contract and in such an instance, the EMD will be forfeited. Performance Guarantee will be forfeited in case of any deviation is found for violating any terms and conditions of tender. On due performance and completion of the contract in all respects, the Security Deposit will be returned to the contractor without any interest.

4. BID OPENING PROCEDURE:

The Technical Bids will be opened by a committee nominated by the Competent Authority from www.eprocure.gov.in website. The Financial Bids of such of those Bidders, who have qualified in the Technical Bid stage by the Evaluation Committee, will be taken up for after finalization of the Technical Bid opening process. L-1 Bidder will be selected by the system automatically.

5. RIGHT OF ACCEPTANCE:

The Principal, Bharati College reserves the right to accept or reject any bid and to annual the bidding process and reject all bids at any time, without thereby incurring any liability to the affected bidder(s) or any obligations to inform the affected Bidder(s) of the grounds for such action. Any failure on the part of the bidder to observe the prescribed procedure and any attempt to canvassfor the work shall render bids liable for rejection. In case of any failure to comply with the provisions of the terms & conditions mentioned, by the bidder that has been awarded the contract, the Competent Authority reserves the right to award the contract to the next eligible bidder and the performance guarantee will be forfeited.

HEAD- : Supply and Installation of Video Surveillance with CCTV System (IP BASED) with allied accessories					
Sr · N o.	ITEMS	Specification	QTY	Per Unit Price (in Rupees) inclusive all taxes	Total Unit Price (In Rs.) inclusive all taxes)
1	32 CHANNEL NVR (2 SATA)	Processor: Industrial-grade processor Operating System: Embedded LINUX IP Camera Input: 32 channel User Interface: Web, Local GUI AI by Camera: Face detection, Face recognition, Perimeter protection, SMD Plus, People counting, Stereo analysis, Heat map AI by NVR: SMD Plus Perimeter Performance of AI by Camera: 6 Channels Video Output: 1 HDMI, 1 VGA Simultaneous: HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 Heterogeneous: HDMI: 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 Face Attributes: Gender, Age group, Glasses, Expressions, Face mask, Beard Abnormality Alarm: Camera disconnection, Storage error, Disk full, IP conflict, MAC conflict, Login locked, Cybersecurity exception SMD Plus by Camera: 6 Channels SMD Plus by NVR: 2 channels: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and lighting condition change Face Recognition AI by NVR: 6 Channels Face Detection AI by Camera: 6 Channels Resolution: 12 MP, 8 MP, 6 MP, 5 MP, 4 MP, 3 MP, 2MP, 960p, 720p, D1, CIF, QCIF	2		

		Decoding Capability: AI disabled: 1 Channel 12 MP@30 fps, 2 Channel 8 MP@30 fps, 3 Channel 5 MP@30 fps, 4 Channel 4 MP@30 fps, 8 Channel 1080p@30 fps AI enabled: 1 Channel 12 MP@30 fps, 1 Channel 8 MP@30 fps, 2 Channel 5 MP@30 fps, 3 Channel 4 MP@30 fps, 7 Channel 1080p@30 fps Video Compression: Insta stream; H.265, H.264+, H.264		
2	16 CHANNEL NVR (2 SATA)	Processor: Industrial-grade processor IP Camera Input: 16 Channels Operating System: Embedded LINUX User Interface: Web, Local GUI AI by Camera: Face detection, Face recognition, Perimeter protection, SMD Plus, ANPR, People counting, Stereo analysis, Heat map AI by NVR: Face detection, Face recognition, Perimeter protection and SMD Plus Perimeter Performance AI by NVR: 2 channels, 10 IVS rules for each channel Perimeter Performance of AI by Camera: All channels (8 targets/s) Face Detection AI by NVR: 1 Channel (up to 12 face images/s each channel) Video Output: 1 HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720; 1 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 Face Attributes: Gender, Age group, Glasses, Expressions, Face mask, Beard Abnormality Alarm: Camera disconnection, Storage error, Disk full, IP conflict, MAC conflict, Login locked, Cyber security exception Face Database Capacity: Up to 10 face databases with 20,000 images, with a total capacity of 2.5 G. Name, Gender, Birthday,	2	

		Address, Credential type, Credential No., Countries & Regions and state can be added to each face image Face Recognition AI by NVR: 8 Channel FD (by camera) + FR (by NVR), image stream: 12 face images/s 1 Channel FD (by NVR) + FR (by NVR), video stream: 12 face images/s Face Recognition AI by Camera : All Channels (8 targets/s) Face Detection AI by Camera: All Channels (8 targets/s) Network Bandwidth: AI disabled: 256 Mbps incoming, 256 Mbps recording and 256 Mbps outgoing AI enabled: 180 Mbps incoming, 180 Mbps recording and 180 Mbps outgoing		
3	HARD DISK 8 TB SATA W D PURPPLE SURVELIAN CE 3 YEARS WARRANT Y	SURVEILLANCE HARD DRIVE: 8TB Model Number: WD85PURZ Formatted capacity: 8TB Form factor: 3.5-inch Advanced Format (AF): Yes Recording Technology: CMR Interface: SATA 6Gb/s RoHS compliant:2 Yes Product Features Cameras supported: Up to 64 HD Maximum Drive Bays Supported: 16 Firmware Feature Name: All Frame Tarnish resistant components: Yes RV Sensors: Yes Performance Interface: transfer rate (max) ⁴ Buffer to host Host to/from drive (sustained): 6 Gb/s 215 MB/s Cache (MB) ¹ : 256 Reliability/Data Integrity Load/unload cycles ⁶ : 300 Annualized workload rating ⁷ : 180TB/yr	6	
4	IP CAMERA INDOOR/OU TDOOR	Effective Pixels 1920(H) x 1080(V) S/N Ratio >56dB Gain Control (AGC) Auto/Manual ROI Yes (4 areas)	96	

Lens 3.6mm (2.8mm Optional) Lens Type Fixed-focal Angle of View 3.6mm: Horizontal: 88°; Vertical: 47°; Diagonal: 104° 2.8mm: Horizontal: 102°; Vertical: 54°; Diagonal: 1020° DORI Distance 3.6mm— 49.7m (Detect) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm— 38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.2.65: 12 Kbps—6144 Kbps H.2.64: 32 Kbps—6144 Kbps Video Streaming Main stream: 1920 × 1080@1—25/30fps; Sub stream: 704 × 576@1—25fps 704 × 480@1 30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethemet.R.J-45 (10100Base—T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity); 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg	1 1				I	
Angle of View 3.6mm: Horizontal: 88°; Vertical: 47°; Diagonal: 104° 2.8mm: Horizontal: 102°; Vertical: 54°; Diagonal: 120° DORI Distance 3.6mm 49.7m (Detect) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm-38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps 6144 Kbps Video Streaming Main stream: 1920 × 1080@1 25/30fps; Sub stream: 704 × 576@1 25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (POE) Weight:0.22kg						
Horizontal: 104° 2.8mm: Horizontal: 102°; Vertical: 54°; Diagonal: 120° DORI Distance 3.6mm – 49.7m (Detcet) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm – 38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps=6144 Kbps H.264: 32 Kbps=6144 Kbps Video Streaming Main stream: 1920 × 1080@1 – 25/30fps; Sub stream: 704 × 576@1 - 25fps 704 × 480@1 – 30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity); 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			Lens Type Fixed-focal			
Diagonal: 104° 2.8mm: Horizontal: 102°; Vertical: 54°; Diagonal: 120° DORI Distance 3.6mm-49.7m (Detect) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm-38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps 6144 Kbps H.264: 32 Kbps 6144 Kbps Wideo Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			Angle of View 3.6mm:			
Horizontal: 102°; Vertical: 54°; Diagonal: 120° DORI Distance 3.6mm- 49.7m (Detect) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm- 38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Wideo Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity); 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			Horizontal: 88°; Vertical: 47°;			
Horizontal: 102°; Vertical: 54°; Diagonal: 120° DORI Distance 3.6mm- 49.7m (Detect) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm- 38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Wideo Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity); 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			Diagonal: 104° 2.8mm:			
Diagonal: 120° DORI Distance 3.6mm—49.7m (Detect) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm—38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps—6144 Kbps H.264: 32 Kbps—6144 Kbps Wideo Streaming Main stream: 1920 × 1080@1—25/30fps; Sub stream: 704 × 576@1—25fps 704 × 480@1—30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mt; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			_			
DORI Distance 3.6mm - 49.7m (Detect) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm - 38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Video Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mt; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1W (POE) Weight:0.22kg						
(Detect) 19.9m (Observe) 9.9m (Recognize) 5m (Identify) 2.8mm - 38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 arca, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Video Streaming Main stream: 1920 × 1080@1−25/30fps; Sub stream: 704 × 576@1−25fps 704 × 480@1−30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:R1-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (POE) Weight:0.22kg						
(Recognize) 5m (Identify) 2.8mm-38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off/ On (4 area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Video Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:R1-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
2.8mm 38.6m (Detect) 15.4m (Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Video Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: 1P67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
(Observe) 7.7m (Recognize) 3.9m (Id Motion Detection Off / On (4) area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Video Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 24 (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `			
3.9m (Id Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Video Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			` · · · · · · · · · · · · · · · · · · ·			
Motion Detection Off / On (4 area, Rectangle) Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Video Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `			
area, Rectangle) Bit Rate H.265: 12 Kbps—6144 Kbps H.264: 32 Kbps—6144 Kbps Video Streaming Main stream: 1920 × 1080@1–25/30fps; Sub stream: 704 × 576@1–25fps 704 × 480@1–30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet: RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°c to +60°C (-40°t to +140°t) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight: 0.22kg			`			
Bit Rate H.265: 12 Kbps-6144 Kbps H.264: 32 Kbps-6144 Kbps Video Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet: RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight: 0.22kg			`			
Kbps H.264: 32 Kbps–6144 Kbps Video Streaming Main stream: 1920 × 1080@1–25/30fps; Sub stream: 704 × 576@1–25fps 704 × 480@1–30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			9 /			
Kbps Video Streaming Main stream: 1920 × 1080@1-25/30fps; Sub stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			=			
Video Streaming Main stream: 1920 × 1080@1–25/30fps; Sub stream: 704 × 576@1–25fps 704 × 480@1–30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			Kbps H.264: 32 Kbps-6144			
1920 × 1080@1–25/30fps; Sub stream: 704 × 576@1–25fps 704 × 480@1–30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			Kbps			
1920 × 1080@1–25/30fps; Sub stream: 704 × 576@1–25fps 704 × 480@1–30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			Video Streaming Main stream:			
stream: 704 × 576@1-25fps 704 × 480@1-30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight: 0.22kg			=			
× 480@1–30fps *The values above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; configuration encryption; bigest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			<u> </u>			
above are the max. frame rates of be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
be subjected to the total encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			<u> </u>			
encoding capacity. Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
Alarm Event: Network disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			•			
disconnection; IP conflict; illegal access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			C 1 0			
access; motion detection; video tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
tampering; security exception Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			_			
Smart Phone: iPhone, iPad, Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
Android Phone Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
Audio Compression: G.711A; G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
G.711Mu; G.726 Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
Cyber Security: Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			1			
encryption; configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
configuration encryption; Digest; WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			Cyber Security: Video			
WSSE; account lockout; security logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
logs; generation and importing of X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			WSSE; account lockout; security			
X.509 certification; HTTP Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			logs; generation and importing of			
Ethernet:RJ-45 (10/100Base-T) Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			_ = =			
Weatherproof Standard: IP67 Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			-			
Operating Temperature -40°C to +60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			,			
+60°C (-40°F to +140°F) Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			±			
Humidity less than ≤ 95% Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			1 0 1			
Power Consumption 1.2W (12V DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg			· · · · · · · · · · · · · · · · · · ·			
DC); 2W (PoE) Max. (ICR + H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
H.265 + IR intensity): 3.2 W (12 VDC); 4.1 W (PoE) Weight:0.22kg						
VDC); 4.1 W (PoE) Weight:0.22kg			, , , , , , , , , , , , , , , , , , , ,			
Weight:0.22kg			• /			
			, ,			
	-		-			
Uplink Ports: 2, 1000Mbps;			•			
POE Transmission Distance: 0-100m	_	POE		-		
5 SWITCH 4+2 Network Standard: 5 .	5			5		
IEEE802.31/802.3\(\frac{1}{8}\)0						
ab			ab			

		Switch Capacity: 12 Gbps Full duplex		
		Packet Forwarding Rate:		
		1.488Mpps/port		
		PoE Ports: 4, 1000Mbps; RJ45		
		ports; Max. 30W Output of Single PoE Port Transmission		
		distance:0~100m		
		Network Ports : 6		
		MAC Address Table : 2K		
		Transmission Distance : 0-		
		100m/100Mbps		
		PoE Standard: IEEE802.3af,		
		IEEE802.3at		
		PoE Power Supply : 1/2(+), 3/6(-		
		PoE Power Budget : 48W		
		PoE Feature : All ports support MDI/MDIX		
		VLAN : Support		
		Watchdog: Support		
		Power Indicator : Light on:		
		Powering Light off: No Power		
		VLAN Indicator: Green light		
		on: VLAN mode Light off: normal mode		
		Port 1-10 indicator : Light off:		
		Link is disconnected		
		Red light on: Powering but data		
		disconnected Light flash quickly:		
		Data Transmitting		
		Forwarding Mode : Store-and-		
		forward		
		PoE Standard : IEEE802.3 10Base-T, IEEE802.3u 100Base-		
		TX, IEEE802.3ab 1000Base-T,		
		IEEE802.1W Spanning		
		Tree, IEEE 802.3x flow control		
		Data Transmission Port : 1×8		
		RJ45, 1×2 RJ45		
		Transmission Rate: 10/100Mbps		
		auto-negotiate,		
	POE	10/100/1000Mbps auto-negotiate	1.5	
6	SWITCH 8+2	Transmission Distance : 10Base- T: ≤250m (CAT3,4,5 UTP),	15	
		1: ≤250m (CA15,4,5 U1P), 100Base-TX: ≤100m (CAT3,4,5		
		UTP), 1000Base-T: ≤100m		
		(CAT3,4,5 UTP)		
		Forwarding Mode : Store and		
		forward		
		Transmission mode : Support		
		Half/Full duplex Mode		
		MAC Address List :2K		
		Case space : 1Mb		

		Jumbo Frame: 9216b Packet Forwarding Rate: 4.1664Mpps@64byte Bandwidth: 5.6G Power Indicator: Green power Ethernet indicator: Yellow, Per Ethernet Port DIP switch indicator: Green per PoE port, Green per uplink port DIP switch:100m:Standard mode - All ports can communicate with each other, 250m: Extend mode, port 1-8 are isolated from each other, transmission distance can up to 250m, and can communicate with port 9-10 Power Input: AC100~240V, 50Hz Power Consumption: Standby: ≤3W, whole: ≤96W PoE Pin: 1/2+, 3/6- The Port max. Rate: ≤25.4W		
7	D-LINK CAT 6 CABLE COPPER 100 MTR	Category: 6 UTP Solid cable Conductor: Conductor: 23 AWG (Solid) Conductor Meta: Conductor Meta: Bare Copper Insulation Material: HD-PE OD: 6.1mm ±0.2 Resistance Unbalance: 5% Max Capacitance Unbalance: 330pF/100m Delay Skew: <45nS	13	
8	RK CONDUIET PIPE 20 MM 40 PCS PER BNDL	Product Features RNS ID: RS051292 Brand Name: Standard Warranty: N/A Material: PVC Size (mm): 20 MM Length (mtr): 3 Mtr	11	

9	4 U RACK WITH FASTNER (EACH FLOOR)	 DVR walls Mount is specially designed to safeguard our DVRs from Theft. Width 550mm & Depth 350mm. Basic frame: CRCA (MS SHEET) 0.6mm to 0.65mm thickness with toughened glass. Construction—Welded. Top & Bottom cover: cable entry cut-outs. Front Door: Lockable—Toughened glass with Lock & Key. Toughened Glass used as an excellent thief deterrent. PDU 3 Sockets (5amp). Standard finish: Powder coated. Dual-Tone Gray Color - fits in well with all indoor/outdoor aesthetics. Differentiator Quality. Load Bearing Capacity - 15kg. Industry leading design. 	20	
10	ELECTRIC SWITCH BOARD	ELECTRIC SWITCH BOARD as per site requirement	20	
11	ELECTRIC WIRE (90 MTR) (APPROX)	Brand: Standard Product Category: Housing Wires Size:1 Sq mm Core: Single and Multicore Cables Length:90 mtr Approx. Net Weight:1.3 Kg Conductor Material: Copper Color option: Green, Red, Yellow, Blue, Black Grade:1100V Material: PVC Insulated Current Rating AC:11 Amp Number/Nom. Dia of wire (mm):32/0.21 Thickness of Insulation (Nom.):0.6 mm Certification:IS:694:2010 Country of Origin: Made in India	8	
12	CAMERA BOX	Technical Details: Material: Polyvinyl chloride Brand: Standard Color: White Style: PVC CCTC Cameras Mounting Boxes Product Dimensions: 12.7D x	96	

		12.7W x 4.5H Centimeter		
13	RJ 45 CONNECTO R BOX	Brand: Standard Connector Type:RJ45 Cable Type :Ethernet Compatible Devices:Switch, Computer, Router, Networking Device Recommended Uses :For Product Networking Ethernet cable category:Cat 6 Color:Green/orange Connector Gender:Male-to-Male Shape:Flat Number of Pins:8 Net Quantity:50 count Gauge:24.0 Indoor/Outdoor Usage:Indoor Package Dimensions:14.1 x 7.2 x 6.4 cm; 150 g Memory Storage Capacity:1 GB Item Weight:150 g	3	
14	LED TV 32 INCH	Brand: Standard Manufacturer: Make In India Model Year: Latest Product Dimensions: 8.3 x 73.17 x 43.92 cm; 3.8 kg Memory Storage Capacity: 8 GB Ram Memory Installed Size: 1.5 GB Operating System: Tizen Hardware Interface: USB, HDMI Graphics Coprocessor: Hyper Real Tuner Technology: DVB-T2 Response Time: 8 Milliseconds Resolution: 1366x768 Compatible Devices: Gaming Console Special Features: HD Picture Quality Hot Keys for quick access of Mounting Hardware :1 LED TV, 1 User Manual, 1 Warranty Card, 1 Remote Control: 2 AAA Batteries, Wall Mount / Table Top will be provided at	4	

		the time of installation based on customer preferences. Number of items:1 Remote Control Display Technology:LED Standing screen display size:32 Inches Display Type:HDR Color Screen5/28/2025 Yes Viewing Angle:178 Degrees Image Aspect Ratio 5/28/202516:09 Image contrast ratio:High Supported image types: JPEG Aspect Ratio:16:9 Screen Resolution:1366 x 768 pixels Resolution:1366 x 768 Pixel Audio Wattage:20 Watts Voltage:240 Volts Wattage:20 Watts Power Source:AC Batteries Required:No Product information Refresh Rate:60 Hz Total USB ports:1 Connector Type:Wi-Fi, USB, Ethernet, HDMI Mounting Type:Wall Mount & Table Mount Includes remote: Yes Supports Bluetooth Technology:No Item Weight:3 kg 800		
15	Conduct PIPE LABOUR CHARGES WITH ALL ACCESSORI ES	Conduct PIPE LABOUR CHARGES WITH ALL ACCESSORIES	3	
16	LAYING WIRE & CAMERA SETUP INSTALLAT ION CHARGES	LAYING WIRE & CAMERA SETUP INSTALLATION CHARGES	3	

• Rates should be inclusive of all taxes

Additional terms and conditions

1. <u>Scope of Supply: - (Bid price to include all cost components)</u>: Supply & installation (Installation wherever applicable) of goods.

2. Mandatory terms and conditions.

- <u>a)</u> The supplier will ensure that material used is of the high/approved quality and the finish of the item is of high standard and the store supplied is of genuine pattern of reputed brand and conforming to the given specifications. In case such defects are noticed then necessary action for repair /replacement will be carried out by the bidder at his own cost.
- **b)** The quality of procurement/installation of <u>video surveillance with CCTV</u> System will be checked by the board of the officers/members. The college authorities will have full rights to inspect the work at any stage. The payment will be released only on satisfactory report by board as per approved specifications.
- c) In case of any damage which will arise due to all kind of natural calamities at the time of installation, then damage/maintenance of the procurement/installation of video surveillance with CCTV (NVR system) for college will be carried out by the firm during the warrant period at his own cost. The repair work to be completed within 15 days after reporting by College. If the firm does not rectify the damage/maintenance work, the action for black listing of firm will be initiated.
- d) All supply will be subject to approval by the Principal Bharati College. Supply will be delivered at the college premises (Consignee Location) at the cost of the firm including all taxes as per bid, which will be compared with quality and inspected with ibid specifications. Damaged or inferior items will have to be replaced by the firm at their cost. The items should be delivered at Bharati College as per Gem contract. In case of delay or failure, the liquidity charges will be applicable as 0.5% per week.
- e) Bidders are to go through the bid document carefully to understand the documents required to be submitted as part of the bid. Please note that the number of documents including the names and content of each of the documents that need to be submitted. Any deviations from these may lead to rejection of the bids. Bidders offer is liable to be rejected if they don't upload any of the requisite certificates/documents sought in the Bid documents. ATC and corrigendum of any.
- **f**) After opening of the commercial bid, the L1 vendors will arrange a sample as per desired specifications. On the approval of sample by the principal Bharati College, final quality/items will be supplied by the bidder only. The cost of transportation of sample etc shall be borne by the bidder only.
- g) All components of the CCTV/video surveillance system should preferably be compliant with the 'Make in India' initiative.
- <u>h</u>) The bidders are required to furnish and forward one legible copy of each of the following documents along with their bids. In case of non-receipt of any of the following documents, the bid will be rejected without any intimation and justification.

- (i) Signed and scanned copy of **proof for payment of Earnest Money** and Tender Fees Deposit.
- (ii) GST registration number of the firm.
- (iii) PAN card of the firm/proprietor.
- (iv) ITR copies for the last 3 Financial years (2021-22, 2022-23, 2023-24).
- (v) Minimum average annual turnover of the bidder(for last 3 financial years) 1.00 Cr.
- (vi) Complete postal and email- address and fax/telephone. No.
- (vii) ECS Mandate format should be submitted by bidder for E-Payment) ECS/EFT/Direct Credit/RTGS/NEFT) duly signed by bank (as per appendix A
- (viii) Warranty certificate of the products. Warranty confirmation certificate to be duly signed & stamped by the bidder (If applicable).
- (ix) Every page of the documents attached will be signed by the bidder.
- (x) Copy of tender acceptance letter (signed by the bidder) should be uploaded in bid.
- (xi) Before visiting campus, bidder has to send a mail with details who is visiting with legal proof of Indian citizen ship and a confirmation from the authorities.
- (xii) Copy of "SVC" issued by the Competent Authority of the College within 5 days from the bid publish date.
- (xiii) Scanned Copy of valid Electrical License from the Govt. Authority.
- i) Bidder's offer is liable to be rejected if they don't upload any of the certificate/documents sought in the bid documents, ATC and corrigendum if any.
- <u>i</u>) Principal Bharati College Delhi reserves the right to reject or cancel the subject bid without assigning reason thereof.
- 3. <u>Guarantee & Warranty: -</u> Guarantee & warranty period and clauses must be specifically mentioned against each item

4. Additional Terms and conditions

- a) Seller will provide onsite support at site assistance to prevent the down time.
- b) All details of Guarantee/Warranty and Service/maintenance schedule will be provided by the vendor.
- c) The bidder is advised to visit examine the installation site and obtain all information that may be necessary for preparing the bid. The costs of visiting the site shall be borne by the bidder. The site visit is for clarification of doubts by vendor for better appreciation and quoting price accordingly.
- d) The bidder representative shall be allowed entry upon consignee premises for such visits, only upon the express conditions that the bidder will release the indemnify the buyer and consignee against all liabilities arising out of such visit including death or injury, loss or damage to the property, and any other loss, damage, costs, and expenses incurred as a result of such visit.
- e) The Bidder shall not be entitled to hold any claim against buyer for non-compliance due to lack of any kind of pre-requisite information as it is the sole responsibility of the bidder to obtain all the necessary information with regard to site, surrounding, working conditions, weather etc. on its own before submission of the bid.
- f) The Principal Bharati College shall have the rights to terminate the contract in part or in full in any of the following cases:-
 - (i) By giving the contractor notice of 14 days advance without assigning any reason what so ever.

- (ii) The contractor is declared as bankrupt and become insolvent.
- (iii) The contractor utilizing the services of any Indian/foreign agent in getting this contract paying any commission to such individual /company etc.
- (iv) If the contractor assigns or sublets this contract or if the contract or attempted to do so.
- (v) If the contractor or any of his representatives or his employees are guilty of fraud in respect of the contract, directly or indirectly give or promise to give or offer any bribe, gift, loan reward or advantage, or otherwise to any officers or persons in employment of the Bharati College.
- (vi) If the Contractor declines, neglects or delays to comply with any demand or requisition or in any other way fails to perform or fulfill any condition of the contract.
- (vii) In case of difference in cost (lower cost) is observed the principal, Bharati College shall be entitled to recover from the supplier on demand, any extra expense he may put to in obtaining supplies hereby agreed to be supplied/provisioned from elsewhere in any manner.
- (viii) Seller should ensure material, manual support, ladder and other requirement (if required) is to be managed by him.
- (g) Bidders are required to physically visit the College preferably within 10 days of this Tender's publication to accurately understand the requirements.
- (h) The "SVC" issued by the Competent Authority of Bharati College must be included with the Technical Bid, Failure to include this certificate will result in rejection of the technical Bid.
- (i) <u>Law:</u> the Contract shall be considered and made in accordance with the laws of the Republic of India, The Contract shall be governed by and interpreted in accordance with the laws of the republic of India.
- (j) <u>Non-disclosure of Contract documents:</u> Except with the written consent of the buyer, other party shall not disclose the contract or any provision, specification, plan, design, pattern, sample or information thereof of any third party.
- (k) <u>Penalty for Quality Assurance:</u> In case the contractor fails to commence/ execute the work as stipulated in the contract/ agreement or there is a breath of any terms and conditions of the contact the Bharati College reserves the right to impose the penalty as details below.

OFFENCES	PENALTIES (IN RUPEES)
Indulging in smoking/ drinking/ sleeping or	Rs. 150/- per offence with removal of the
any other misconduct during duty hours by	offender from service.
the bidder/ worker at Bharati College.	
In case the services remain consistently	Warning for termination of Contract and
unsatisfactory for a period of more than one	penalty of 1% of the Bill value will be
week	imposed and deducted
For any other breach, Violation or	Rupees 100/- will be imposed per day
Contravention of any terms and Conditions.	
Any indiscipline act	As decided by the Competent authority of
	the College

- (l) In case of any dispute, the decision of the Principal, Bharati College shall be Final which will be imposed off within the Delhi court jurisdiction only.
- (m) Every page of the documents attached will be signed by the bidder.

MODEL ECS MANDATE FORMAT (FORM DPM-11)

Customers option to received payments through e-Payment (ECS/EFT/DIRECT CREDIT/ RTGS/NEFT/ Other payment mechanism as approved by RBI CREDIT CLEARING MECHANISM

1.	Customer's name
2.	Particulars of Bank Account
	(a) Bank Name
	(b) Branch Name
	(c) Address of Bank
	(d) Telephone numbers of Bank
	(e) IFS code of Bank
	(f) 9 Digit code number of Bank and Branch
	And Branch appearing on MICR cheque issued by Bank
	(g) Account Type (SB Account/ Current Account of Cash)
	(h) Ledger Number
	(i) Ledger Folio Number
	(j) Account number as appearing on cheque Book
3.	Please attach a blank cancelled cheque or photocopy of a cheque or front pager of your
	saving bank passbook issued by your bank for verification of the above particulars.
4.	Date of Effect
	"I, hereby, declare that the particulars given above are correct and complete, If the transaction is delayed or not effected at all for reasons of incomplete or incorrect or incorrect information, I would m=not hold the user institution responsible, I have the option invitation letter and agree to discharge the responsibility expected for me as a participant under scheme".
	()
	Date- signature of Customer
	Certified that the particulars furnished above are correct as per our records.
	Bank's Stamp: () Date Signature of the Authorized Official from the Bank